

Wels, October 6th 2021

OVERSIZING FRONIUS SYMO GEN24 - AUSTRALIA AND NEW ZEALAND

Fronius International GmbH

hereby confirms that the inverters

/ Fronius Symo GEN24 3.0 (Plus)

/ Fronius Symo GEN24 4.0 (Plus)

/ Fronius Symo GEN24 5.0 (Plus)

/ Fronius Symo GEN24 6.0 (Plus)

/ Fronius Symo GEN24 8.0 (Plus)

/ Fronius Symo GEN24 10.0 (Plus)

can be oversized above the rated nameplate capacity without voiding the manufacturer's warranty, provided that the following conditions are always adhered to:

- / The string and array configuration do not exceed the sizing limits of the inverter (I_{sc_max} , P_{pv_max} , U_{dc_max}) stated in the official datasheets and in this document. This includes, but is not limited to conditions like, low temperatures, high irradiances, bifacial gain, etc.
- Exceeding any of these limits can damage the inverter or even cause harm or injury.

INPUT DATA	SYMO GEN24 3.0 (PLUS)	SYMO GEN24 4.0 (PLUS)	SYMO GEN24 5.0 (PLUS)	SYMO GEN24 6.0 (PLUS)	SYMO GEN24 8.0 (PLUS)	SYMO GEN24 10.0 (PLUS)
DC input voltage range (U_{dc_min} - U_{dc_max})			80 - 1 000 V (U _{oc max} of the PV array ≤ 1 000 V)			
Usable MPP input current (MPPT1/MPPT2/total) (I_{dc_max})	12.5 / 12.5 / 25 A	12.5 / 12.5 / 25 A	12.5 / 12.5 / 25 A	25 / 12.5 / 37.5 A	25 / 12.5 / 37.5 A	25 / 12.5 / 37.5 A
Max. PV generator short circuit current (MPPT1/MPPT2/total) (I_{sc_max})	18.75 / 18.75 / 37.5 A	18.75 / 18.75 / 37.5 A	18.75 / 18.75 / 37.5 A	37.5 / 18.75 / 56 A	37.5 / 18.75 / 56 A	37.5 / 18.75 / 56 A
Max. usable DC power (MPPT1/MPPT2/total) (P_{dc_max})	3.15 / 3.15 / 3.15 kW	4.18 / 4.18 / 4.18 kW	5.2 / 5.2 / 5.2 kW	6.22 / 6 / 6.22 kW	7.2 / 6 / 8.26 kW	7.2 / 6 / 10.3 kW
Max. PV generator power (MPPT1/MPPT2/total) (P_{pv_max})	4.5 / 4.5 / 4.5 kWpeak	6 / 6 / 6 kWpeak	6.5 / 6.5 / 7.5 kWpeak	7.2 / 6.5 / 9 kWpeak	7.2 / 7 / 12 kWpeak	7.2 / 7.2 / 14.4 kWpeak
reduced DC input voltage range (U_{dc_min} - U_{dc_max})			80 - 850 V (U _{oc max} *** of the PV array ≤ 850 V)		80 - 750 V (U _{oc max} *** of the PV array ≤ 750 V)	
Max. PV generator power @ reduced DC input voltage range *** (MPPT1/MPPT2/total) (P_{pv_max})	4.5 / 4.5 / 6 kWpeak	6 / 6 / 8 kWpeak	6.5 / 6.5 / 10 kWpeak	7.5 / 6.5 / 12 kWpeak	10 / 7 / 15 kWpeak	12.5 / 7.5 / 15 kWpeak

***Note - the oversizing values in the table vary depending on the PV array max. voltage U_{oc_max} .

Fronius International GmbH

Business Unit Solar Energy
Froniusplatz 1
A-4600 Wels



Bernhard Kossak, MSc
Head of Systems Technology